



XINSHENG
CHEMICAL CO.,LTD

Technical Data Sheet

Product name	ALUMINUM PHOSPHATE
CAS No	7784-30-7
EC No	232-056-9
Chemical formula	AlPO4
Appearance	White Powder
Storage	Keep the product in a tightly closed container ,Isolate from any source of heat or ignition and moisture
Packing unit	25kg Poly Propylene bag & 500kg Poly Propylene bag, Any size customers want.
Application	Mostly used as binder and curing agent in the production of hi-temp refractory materials for kiln. As fluxing agent in the production of special glass, as binder in fabrication of ceramics or tooth, and as catalyst in organic synthesis. Potash water glass cement is made up of potash water glass, condensed aluminum phosphate as curing agent and acid-resistant fillings.
Property	Potash water glass firming agent is superior to sodium silicate cement in impermeability, resistance to dilute acid and cohesive strength.
Characteristics	White Powder. Soluble in acid or alkali solution, insoluble in water or alcohol.

CHEMICAL ANALYSIS

TEST ITEM	UNIT	REQUIREMENT
Whiteness	%	Min 90
Al2O3	wt. %	30-40
P2O5	wt. %	60-70
Moisture	wt. %	Max1.5
Oil absorption	ml/100g	25-35
The PH Value	-	3-5

Factory Dongyang town,xinle city,hebei province,china

Telephone +86-15833937290

Facsimile +86-311-88676379

Email sales@sjzxschem.com

Contacts Daisy

Web site : [Http://www.sjzxschem.com](http://www.sjzxschem.com)



BV SGS CIQ IMDG MSDS